





SPEED MPH	MIN LENGTH (L)
LESS THAN 40	50 FT
40 TO 55	70 FT
60 TO 80	100 FT



END TREATMENT TYPE G



TYPICAL SECTION A-A



TYPICAL SECTION B-B

DESIGN-ONLY NOTES:

- A. APPROVED SYSTEM: MSKT-SP-MGS MANUFACTURED BY ROAD SYSTEMS, INC. REFER TO UDOT GUIDELINES FOR CRASH CUSHIONS AND BARRIER END TREATMENTS FOR SPECIFIC SYSTEM DETAILS.
- B. INSTALL SYSTEM WITH 2 FT OFFSET (25:1 FLARE RATE). SYSTEM TO BE INSTALLED WITH TANGENT BARRIER.
- C. MEET SLOPE REQUIREMENTS IN RECOVERY AREA AS DETAILED IN APPLICABLE UDOT ROADWAY DESIGN MANUALS DWGS. THE ADDITIONAL INFORMATION LISTED BELOW IS THE MINIMUM ACCEPTABLE SLOPE REQUIREMENTS FOR THE APPROACH AREA OF THE END TREATMENT AND THE RECOVERY AREA.
 - 1. APPROACH AREA: THE AREA PRIOR TO IMPACTING A SYSTEM.
 - A) USE 10:1 OR FLATTER FORESLOPES IN APPROACH AREAS.
 - 2. RECOVERY AREA: THE AREA BEHIND THE END TREATMENT AND BARRIER SYSTEM EXTENDING FROM THE APPROACH END OF THE END TREATMENT TO THE END OF THE CALCULATED LENGTH OF NEED.
 - A) USE A 4:1 OR FLATTER FORESLOPE OR BACKSLOPE IN RECOVERY AREA.
 - B) USE A 3:1 FORESLOPE IN RECOVERY AREA IF IT IS IMPRACTICAL TO USE A 4:1 FORESLOPE. ESTABLISH A RECOVERY AREA AT THE TOE OF THE 3:1 FORESLOPE OF 6:1 OR FLATTER TO CLEAR ZONE LIMITS. REFER TO THE UDOT ROADWAY DESIGN MANUAL AND AASHTO ROADSIDE DESIGN GUIDE FOR ADDITIONAL INFORMATION.
 - C) USE A 4:1 OR FLATTER BACKSLOPE IN RECOVERY AREA TO THE CLEAR ZONE LIMIT, IF A 4:1 OR FLATTER BACKSLOPE CANNOT BE PROVIDED A 3:1 IS ACCEPTABLE.
- 3. MATCH ROADWAY GRADE PROFILE TO THE HEAD OF THE SYSTEM INSIDE THE APPROACH AREAS.
- D. USE GUARDRAIL TRANSITION, BA 4 SERIES STD DWGS, WHEN ATTACHING SYSTEM TO CONCRETE BARRIER OR BRIDGE PARAPET.
- E. USE THE AASHTO ROADSIDE DESIGN GUIDE TO ESTABLISH CLEAR ZONE REQUIREMENTS AND LENGTH OF NEED (LON) REQUIREMENTS.
- F. 2 FT MINIMUM BARRIER OFFSET IS OPTIONAL WHEN ROADWAY DESIGN REQUIRES A 12 FT OR WIDER EFFECTIVE SHOULDER.
- G. DO NOT PLACE SIGNS, POSTS, OR OTHER HAZARDS IN APPROACH AREA. USE BREAKAWAY SIGNS OR POSTS WHEN PLACED IN RECOVERY AREA, AND MAINTAIN A MINIMUM 10 FT CLEARANCE TO THE SIDE AND 25 FT FROM THE REAR OF THE SYSTEM. MITIGATE POTENTIAL HAZARDS IN THE RECOVERY AREA.

NOTES:

- 1. REFER TO MANUFACTURER'S SPECIFICATIONS FOR POST, RAIL ELEMENT, AND POST TO RAIL CONNECTION REQUIREMENTS. HAVE SHOP DRAWING AVAILABLE ON SITE FOR REFERENCE DURING INSTALLATION
- 2. COMPLETE SLOPE PREPARATION PRIOR TO INSTALLING SYSTEM.
- 3. CLEAR RECOVERY AND APPROACH AREAS OF ANY FIXED OBJECTS OR HAZARDS.
- 4. CONSTRUCT PLATFORM AS REQUIRED WHEN THE SPACE IS AVAILABLE EVEN IF THE PLATFORM EXTENDS BEYOND THE CLEAR ZONE REQUIREMENTS. SEE STD DWG CC 8C FOR EXCEPTIONS.
 - A) CONSTRUCT 6:1 OR FLATTER SLOPE FOR TRANSVERSE SLOPE FROM APPROACH PAD.
- 5. MOUNT OBJECT MARKER POST PER STD DWG CC 1 END TREATMENT TYPE G.

REVISIONS

NO.	DATE	APPR.	REMARKS

UTAH DEPARTMENT OF TRANSPORTATION
STANDARD DRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION
SALT LAKE CITY, UTAH

RECOMMENDED FOR APPROVAL
[Signature]
CHAIRMAN STANDARDS COMMITTEE
APPROVED
DATE
AUG 30, 2018
DEPUTY DIRECTOR
DATE
AUG 30, 2018

GRADING AND
INSTALLATION DETAILS
MSKT-SP-MGS
END TREATMENT
TYPE G (MASH)

STD. DWG. NO.
CC 8B

SUPPLEMENTAL DRAWING